

JC864 U.S. PTO
09/628661

07/28/00

**UTILITY
PATENT APPLICATION
TRANSMITTAL**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.

862.C1966

First Named Inventor or Application Identifier

NORIIHIRO KAWATOKO, ET AL.

Express Mail Label No.

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231☒ Fee Transmittal Form
(Submit an original, and a duplicate for fee processing)☒ Specification **Total Pages** **76**☒ Drawing(s) (35 USC 113) **Total Sheets** **40**☒ Oath or Declaration **Total Pages** **2**

- a. ☐ Newly executed (original or copy)
b. ☒ Unexecuted for information purposes
c. ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 17 completed)
[Note Box 5 below]

i. ☐ **DELETION OF INVENTOR(S)**
Signed Statement attached deleting inventor(s)
named in the prior application, see 37 CFR
1.63(d)(2) and 1.33(b).

5. ☐ Incorporation By Reference (useable if Box 4c is checked)
The entire disclosure of the prior application, from which a copy of the
oath or declaration is supplied under Box 4c, is considered as being
part of the disclosure of the accompanying application and is hereby
incorporated by reference therein.

6. ☐ Microfiche Computer Program (Appendix)7. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)

- a. ☐ Computer Readable Copy
b. ☐ Paper Copy (identical to computer copy)
c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☐ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
14. ☐ Small Entity Statement(s) ☐ Statement filed in prior application
Status still proper and desired
15. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
16. ☐ Other: _____

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. _____**18. CORRESPONDENCE ADDRESS**☒ Customer Number or Bar Code Label

05514

(Insert Customer No. or Attach bar code label here)

or ☐ Correspondence address below

NAME

Address

City

State

Zip Code

Country

Telephone

Fax

CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
	TOTAL CLAIMS (37 CFR 1.16(c))	33-20 =	13	X \$ 18.00 =	\$ 234.00
	INDEPENDENT CLAIMS (37 cfr 1.16(b))	3-3 =	0	X \$ 78.00 =	\$ 00.00
	MULTIPLE DEPENDENT CLAIMS (if applicable) (37 CFR 1.16(d))			\$ 260.00 =	\$ 00.00
	BASIC FEE (37 CFR 1.16(a))				\$ 690.00
	Total of above Calculations =				\$ 924.00
	Reduction by 50% for filing by small entity (Note 37 CFR 1.9, 1.27, 1.28).				
	TOTAL =				\$ 924.00

19. Small entity status


- a. ☐ A Small entity statement is enclosed
- b. ☐ A small entity statement was filed in the prior nonprovisional application and such status is still proper and desired.
- c. ☐ Is no longer claimed.

20. ☒ A check in the amount of \$ 924.00 to cover the filing fee is enclosed.

21. ☐ A check in the amount of \$ _____ to cover the recordal fee is enclosed.

22. The Commissioner is hereby authorized to credit overpayments or charge the following fees to Deposit Account No. 06-1205:

- a. ☒ Fees required under 37 CFR 1.16.
- b. ☐ Fees required under 37 CFR 1.17.
- c. ☐ Fees required under 37 CFR 1.18.

SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED	
NAME	Mark A. Williamson - Reg. No. 33,628
SIGNATURE	
DATE	July 28, 2000

MAW/vjw

TITLE OF THE INVENTION
PRINTING APPARATUS, CONTROL METHOD OF THE APPARATUS, AND
COMPUTER-READABLE MEMORY

5 FIELD OF THE INVENTION

The present invention relates to a printing apparatus for printing an image by using a printhead having a plurality of printing elements, a control method of the apparatus, and a computer-readable memory.

10 Note that the present invention is applicable not only to a general printing apparatus but also to a copying machine, a facsimile apparatus having a communication system, a word processor having a printing unit, and an industrial printing apparatus combined with
15 various processors.

BACKGROUND OF THE INVENTION

Printing apparatuses such as a printer, a copying machine, and a facsimile apparatus are so constructed as
20 to print an image composed of dot patterns on a printing medium such as a paper sheet or thin plastic plate on the basis of image information. Printing apparatuses like this can be classified, in accordance with printing systems, into an inkjet system, a wire dot system, a
25 thermal system, and a laser beam system. The inkjet system (inkjet printing apparatus) prints an image by

discharging ink (printing solution) droplets from
discharge orifices in a printhead and landing the ink
droplets on a printing medium.

Recently, a large number of printing apparatuses
5 are used, and high-speed printing, high resolution, high
image quality, and low noise are required for these
printing apparatuses. The above inkjet printing
apparatus is an example of a printing apparatus meeting
these requirements. This inkjet printing apparatus
10 prints an image by discharging ink from a printhead, so
noncontacting printing is possible. Hence, the inkjet
printing apparatus can form stable printed images on a
wide variety of printing media.

Of such inkjet printing apparatuses, an apparatus
15 using a method of printing an image by forming ink
droplets by using thermal energy is simple in structure
and hence has the advantage that the density of nozzles
for discharging ink can be readily increased.

Unfortunately, an inkjet printing apparatus
20 requires stable discharge of ink because the apparatus
prints an image by discharging ink from a printhead.
That is, the printhead of an inkjet printing apparatus
must have stable performance with respect to durability,
environments, the printhead temperature, the number of
25 simultaneously discharged ink droplets, and the like.

"Stable discharge" means a stable discharge amount, discharge speed, and discharge state (ink droplet landing position).

For this stabilization, control has been performed
5 such that a driving pulse to be applied to a printhead is changed in accordance with the temperature of a printing apparatus main body or of the printhead.

In conventional apparatuses, the number of discharge energy generating elements to be
10 simultaneously driven changes in accordance with an image to be printed, so an electric current flowing from the power supply of the main body fluctuates. This changes the voltage drop resulting from the resistance of a wire connecting the main body and the printhead.
15 Therefore, when a predetermined voltage is applied to the printhead, the voltage applied to the discharge energy generating elements in the printhead fluctuates for each image to be printed.

For example, in a general inkjet printing
20 apparatus, the wiring resistance between the main body and the printhead is about 0.2 Ω , and the head contact resistance is about 0.1 Ω , so the total resistance is about 0.3 Ω . Assume that a driving current of 100 to 200 mA flows through each discharge energy generating
25 element and twenty-four elements are simultaneously driven, the total current is 2.4 to 4.8 A, and the

voltage drop by the wiring is as high as $0.3 \Omega \times (2.4 \text{ to } 4.8 \text{ A}) = 0.72 \text{ to } 1.44 \text{ V}$. This is the voltage fluctuation applied to the discharge energy generating elements.

This voltage fluctuation applied to the discharge
5 energy generating elements results in fluctuations in
discharge energy, i.e., fluctuations in ink discharge
amount and discharge speed. Consequently, printing
density unevenness or ink droplet landing position
deviation takes place, or no ink droplet is discharged.
10 This significantly degrades the printing quality.

Also, the number of simultaneous ink discharging
nozzles changes the voltage to be applied to a heater of
each nozzle of the printhead. A driving voltage and a
driving pulse are so determined that ink droplets are
15 stably discharged even when the number of simultaneous
ink discharging nozzles is a maximum, i.e., even when
the driving voltage is a maximum. When the number of
simultaneous ink discharging nozzles is small, therefore,
an excess driving voltage or an excess pulse width of a
20 driving pulse is applied to the heaters, and this
degrades the durability.

To solve these problems, diverse methods have been
conventionally proposed.

For example, Japanese Patent Laid-Open No. 58-5280
25 has proposed a thermal dot printing apparatus which
changes the driving pulse width and the driving interval

in accordance with the number of dots to be simultaneously driven.

Also, Japanese Patent Laid-Open No. 5-96771 has proposed a thermal transfer printing apparatus which
5 changes the driving time by detecting the number of resistors to be powered in order to correct the voltage drop in a common wiring portion.

Japanese Patent Laid-Open No. 5-116342 has proposed an inkjet printing apparatus in which a
10 detecting unit using an MPU and a RAM detects the number of dots to be simultaneously discharged and the driving voltage is controlled by using the detection result.

Japanese Patent Laid-Open No. 9-11463 has proposed an inkjet printing apparatus in which an image signal
15 from a host apparatus or the like is temporarily stored in a buffer and converted into a bit signal for each heat-generating resistor in an inkjet printhead by an image processing circuit, and the driving pulse conditions are determined by using a lookup table on the
20 basis of the number of dots to be discharged, the positions of nozzles, and temperature information obtained from a thermistor added to the inkjet printhead.

Furthermore, Japanese Patent Laid-Open No. 9-11504 has proposed an inkjet printing apparatus which counts
25 the number of nozzles to be simultaneously driven in a printhead, stores driving parameters in a RAM on the

basis of this counted value, and uses these stored driving parameters.

The foregoing are the conventional examples of driving pulse width control for improving the printing stability and the conventional examples of driving pulse width control based on the number of simultaneous ink discharging nozzles. As described above, driving pulse width control is performed for various purposes. When the driving pulse width is changed in accordance with the temperature, the voltage drop by simultaneous discharge also changes. This complicates the process of appropriate control. Also, while the driving frequency of a printhead increases from ten-odd KHz to several tens of KHz with recent improvements in printing speed and printing quality, the amount of printing data is increasing. This makes the conventional method of previously counting printing data difficult to perform.

SUMMARY OF THE INVENTION

The present invention has been made in consideration of the above problems, and has as its object to provide a printing apparatus capable of stable printing, a control method of the apparatus, and a computer-readable memory.

A printing apparatus according to the present invention for achieving the above object has the following arrangement.

A printing apparatus for performing printing by
5 using a printhead having a plurality of printing
elements comprises discriminating means for
discriminating the number of simultaneously driven
printing elements of the plurality of printing elements
when printing data is printed, and control means for
10 controlling a driving pulse to be applied to printing
elements used in the printing of the printing data, on
the basis of a fundamental pulse width changeably
determined on the basis of driving conditions of the
printhead and the number of simultaneously driven
15 printing elements discriminated by the discriminating
means.

Preferably, the driving conditions include a
wiring resistance, heater resistance, driving TrON
resistance, and environmental temperature of the
20 printhead.

Preferably, the control means comprises storage
means for storing a first management table for managing
the correspondence of the driving conditions with the
fundamental pulse width, and a second management table
25 for managing the correspondence of the fundamental pulse
width with a change amount of the fundamental pulse

width based on the number of simultaneously driven
printing elements, first determining means for
determining a fundamental pulse width corresponding to
the driving conditions by looking up the first
5 management table, and second determining means for
determining a change amount of the fundamental pulse
width, which corresponds to the number of simultaneously
driven printing elements, by looking up the second
management table, and changes the fundamental pulse
10 width determined by the first determining means by the
change amount determined by the second determining means
to generate a driving pulse to be applied to printing
elements used in the printing of the printing data.

Preferably, the control means defines the
15 fundamental pulse width by one of leading and trailing
edges of a pulse signal on the basis of the driving
conditions, and controls a driving pulse width of a
driving pulse to be applied to printing elements by the
other, on the basis of the number of simultaneously
20 driven printing elements.

Preferably, the control means comprises storage
means for storing a third management table for managing
the correspondence of rise time and fall time of the
heat pulse, the driving conditions, and the fundamental
25 pulse width, and controls a pulse width of the driving
pulse corresponding to the number of simultaneously

driven printing elements and the driving conditions by looking up the third management table.

Preferably, the printing apparatus comprises a plurality of printheads, and if power lines for
5 supplying power to the printheads are independent of each other, the control means executes the control for each power line.

Preferably, the control means makes a change amount for the driving pulse, which the control means
10 generates by changing a pulse width of the fundamental pulse when the number of simultaneously driven printing elements is equal to or larger than a predetermined value, smaller than a change amount for the driving pulse, which the control means generates by changing a
15 pulse width of the fundamental pulse when the number of simultaneously driven printing elements is less than the predetermined value.

Preferably, the control means makes a change amount for the driving pulse, which the control means
20 generates by changing a pulse width of the fundamental pulse when the number of simultaneously driven printing elements is equal to or smaller than a predetermined value, larger than a change amount for the driving pulse, which the control means generates by changing a pulse
25 width of the fundamental pulse when the number of

simultaneously driven printing elements is less than the predetermined value.

Preferably, if the number of simultaneously driven printing elements for use in predischARGE of the printhead is limited, the control means makes a pulse width of a driving pulse to be applied to printing elements used in the predischARGE larger than a pulse width of a driving pulse to be applied to printing elements for use in printing which uses printing elements equal or larger in number to or than the number of simultaneously driven printing elements.

Preferably, when predischARGE of the printhead is to be performed, the control means applies a driving pulse having a predetermined width to printing elements used in the predischARGE.

Preferably, the fundamental pulse width is a fundamental pulse width selected and determined from a plurality of fundamental pulse widths.

Preferably, the driving conditions are conditions including printhead characteristics.

Preferably, the second management table holds as an index value a change in fundamental pulse width which is based on the number of simultaneously driven printing elements.

Preferably, a fourth management table representing a relationship between the change in fundamental pulse

width and the index value, the fourth management table being prepared for each printing mode.

Preferably, the printing mode is a mode for performing printing complementarily in accordance with a printing pass count.

A method of controlling a printing apparatus according to the present invention for achieving the above object has the following steps.

A method of controlling a printing apparatus for performing printing by using a printhead having a plurality of printing elements comprises the discrimination step of discriminating the number of simultaneously driven printing elements of the plurality of printing elements when printing data is printed, and the control step of controlling a driving pulse to be applied to printing elements used in the printing of the printing data, on the basis of the number of simultaneously driven printing elements discriminated in the discrimination step and a fundamental pulse width determined on the basis of driving conditions of the printhead.

A computer-readable memory according to the present invention for achieving the above object has the following program codes.

A computer-readable memory storing program codes of control of a printing apparatus for performing

printing by using a printhead having a plurality of
printing elements comprises a program code of the
discrimination step of discriminating the number of
simultaneously driven printing elements of the plurality
5 of printing elements when printing data is printed, and
a program code of the control step of controlling a
driving pulse to be applied to printing elements used in
the printing of the printing data, on the basis of the
number of simultaneously driven printing elements
10 discriminated in the discrimination step and a
fundamental pulse width determined on the basis of
driving conditions of the printhead.

Other features and advantages of the present
invention will be apparent from the following
15 description taken in conjunction with the accompanying
drawings, in which like reference characters designate
the same or similar parts throughout the figures thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

20 Fig. 1 is a perspective view showing the external
appearance of an inkjet printer according to an
embodiment of the present invention;

Fig. 2 is a perspective view showing the state in
which external parts of the printer shown in Fig. 1 are
25 removed;

Fig. 3 is an exploded perspective view showing a printhead cartridge used in the embodiment of the present invention;

Fig. 4 is a side view showing the state in which
5 the printhead cartridge shown in Fig. 3 is assembled;

Fig. 5 is a perspective view showing the printhead of Fig. 4 when obliquely viewed from below;

Figs. 6A and 6B are perspective views showing a scanner cartridge in the embodiment of the present
10 invention;

Fig. 7 is a block diagram schematically showing the overall arrangement of an electronic circuit in the embodiment of the present invention;

Fig. 8 is a block diagram showing the internal
15 arrangement of a main PCB shown in Fig. 7;

Fig. 9 is a block diagram showing the internal arrangement of an ASIC shown in Fig. 8;

Fig. 10 is a flow chart showing the operation of the embodiment of the present invention;

Fig. 11 is a view showing a discharge nozzle
20 driving circuit of the first embodiment;

Fig. 12 is a timing chart showing the driving timings of the discharge nozzle driving circuit of the first embodiment shown in Fig. 11;

Fig. 13 is a view showing a power supply path of a
25 general inkjet printing apparatus;

Fig. 14 is a view showing a power supply path when the number of simultaneous ink discharging nozzles is N;

Fig. 15 is a graph showing the relationship between the number of simultaneous ink discharging
5 nozzles and the pulse width;

Fig. 16 is a view showing a conventional driving pulse width table;

Fig. 17 is a view showing a conventional pulse width LUT for modulating the driving pulse width on the
10 basis of the number of simultaneous ink discharging nozzles;

Fig. 18 is a view showing a driving pulse width table of the first embodiment;

Fig. 19 is a view showing another driving pulse
15 width table of the first embodiment;

Fig. 20 is a view showing still another driving pulse width table of the first embodiment;

Fig. 21 is a block diagram of a driving signal generating circuit of the first embodiment;

20 Fig. 22 is a timing chart showing the driving timings of the driving signal generating circuit of the first embodiment;

Fig. 23 is a view showing an example of a driving pulse setting method of the first embodiment;

25 Fig. 24 is a view showing a driving pulse width table with respect to Fig. 23 of the first embodiment;

Fig. 25 is a view showing another driving pulse width table with respect to Fig. 23 of the first embodiment;

Fig. 26 is a view showing still another driving pulse width table with respect to Fig. 23 of the first embodiment;

Fig. 27 is a view showing still another driving pulse width table with respect to Fig. 23 of the first embodiment;

Fig. 28 is a view showing still another driving pulse width table with respect to Fig. 23 of the first embodiment;

Fig. 29 is a flow chart showing processing executed in the first embodiment;

Fig. 30 is a view showing a power supply path of an inkjet printing apparatus of the second embodiment;

Fig. 31 is a view showing a power supply path in a printhead of the second embodiment;

Fig. 32 is a graph showing the relationship between the number of simultaneous ink discharging nozzles and the pulse width when the pulse width is narrowed for the number of simultaneous ink discharging nozzles equal to or larger than the upper limit in the second embodiment;

Fig. 33 is a view showing a driving pulse width table with respect to Fig. 32 of the second embodiment;

Fig. 34 is a view showing an example in which the number of simultaneous ink discharging nozzles = 8 is uniformly distributed;

Fig. 35 is a view showing a case in which the number of simultaneous ink discharging nozzles = 8 is concentrated to one chip;

Fig. 36 is a graph showing the relationship between the number of simultaneous ink discharging nozzles and the pulse width when the pulse width is increased for a small number of simultaneous ink discharging nozzles by taking account of one-pass printing in the second embodiment; and

Fig. 37 is a view showing a driving pulse width table with respect to Fig. 36 of the second embodiment.

Fig. 38 is a view showing a driving pulse width table of the second embodiment.

Fig. 39 is a view showing a driving pulse width table of the second embodiment.

Fig. 40 is a view showing a driving pulse width table of the second embodiment.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiments according to a printing apparatus of the present invention will be described below with reference to the accompanying drawings.

In the embodiments to be explained below, a printing apparatus using an inkjet printing system will be described by taking a printer as an example.

In this specification, "print" is not only to form
5 significant information such as characters and graphics
but also to form, e.g., images, figures, and patterns on
printing media in a broad sense, regardless of whether
the information formed is significant or insignificant
or whether the information formed is visualized so that
10 a human can visually perceive it, or to process printing
media.

"Printing media" are any media capable of
receiving ink, such as cloth, plastic films, metal
plates, glass, ceramics, wood, and leather, as well as
15 paper sheets used in common printing apparatuses.

Furthermore, "ink" (to be also referred to as a
"liquid" hereinafter) should be broadly interpreted like
the definition of "print" described above. That is, ink
is a liquid which is applied onto a printing medium and
20 thereby can be used to form images, figures, and
patterns, to process the printing medium, or to process
ink (e.g., to solidify or insolubilize a colorant in ink
applied to a printing medium).

[Apparatus Main Body]

25 Figs. 1 and 2 show an outline of the arrangement
of a printer using an inkjet printing system. Referring

to Fig. 1, an apparatus main body M1000 as a shell of the printer according to this embodiment is composed of external members, i.e., a lower case M1001, upper case M1002, access cover M1003, and delivery tray M1004, and
5 a chassis M3019 (Fig. 2) accommodated in these external members.

The chassis M3019 is made of a plurality of plate-like metal members having predetermined stiffness, forms a framework of the printing apparatus, and holds
10 various printing mechanisms to be described later.

The lower case M1001 forms a substantially lower half of the apparatus main body M1000, and the upper case M1002 forms a substantially upper half of the apparatus main body M1000. The combination of these two
15 cases forms a hollow structure having a housing space for housing diverse mechanisms to be described later. Openings are formed in the top surface and the front surface of this hollow structure.

One end portion of the delivery tray M1004 is
20 rotatably held by the lower case M1001. By rotating this delivery tray M1004, the opening formed in the front surface of the lower case M1001 can be opened and closed. When printing is to be executed, therefore, the delivery tray M1004 is rotated forward to open the opening to
25 allow printing sheets to be delivered from this opening, and delivered printing sheets P can be stacked in order.

Also, the delivery tray M1004 accommodates two auxiliary trays M1004a and M1004b. By pulling each tray forward as needed, the sheet support area can be increased and reduced in three steps.

5 One end portion of the access cover M1003 is rotatably held by the upper case M1002. This allows this access cover M1003 to open and close the opening formed in the top surface of the upper case M1002. By opening this access cover M1003, a printhead cartridge H1000 or
10 an ink tank H1900 housed inside the main body can be replaced. Although not shown, when the access cover M1003 is opened or closed, a projection formed on the rear surface of this access cover M1003 rotates a cover opening/closing lever. A microswitch or the like detects
15 the rotated position of this lever. In this way, the open/closed state of the access cover can be detected.

 On the top surface in the rear portion of the upper case M1002, a power key E0018 and a resume key E0019 are arranged to be able to be pressed, and an LED
20 E0020 is also arranged. When the power key E0018 is pressed, the LED E0020 is turned on to inform the operator that printing is possible. This LED E0020 has various display functions, e.g., informs the operator of a trouble of the printer by changing the way the LED
25 E0020 turns on and off, changing the color of light, or sounding a buzzer E0021 (Fig. 7). When the trouble is

solved, printing is restarted by pressing the resume key E0019.

[Printing Mechanisms]

Printing mechanisms of this embodiment housed in
5 and held by the apparatus main body M1000 of the above printer will be described below.

The printing mechanisms according to this
embodiment are: an automatic feeder M3022 for
automatically feeding the printing sheets P into the
10 apparatus main body; a conveyor unit M3029 for guiding
the printing sheets P fed one by one from the automatic
feeder to a desired printing position and guiding these
recording sheets P from the printing position to a
delivery unit M3030; a printing unit for performing
15 desired printing on each printing sheet P conveyed by
the conveyor unit M3029; and a recovery unit (M5000) for
recovering, e.g., the printing unit.

(Printing Unit)

The printing unit will be described below.

20 This printing unit includes a carriage M4001
movably supported by a carriage shaft M4021, and the
printhead cartridge H1000 detachably mounted on this
carriage M4001.

Printhead Cartridge

25 First, the printhead cartridge will be described
with reference to Figs. 3 to 5.

As shown in Fig. 3, the printhead cartridge H1000 of this embodiment has the ink tank H1900 containing ink and a printhead H1001 for discharging the ink supplied from this ink tank H1900 from nozzles in accordance with printing information. This printhead H1001 is of a so-called cartridge type detachably mounted on the carriage M4001 (to be described later).

To make photographic high-quality color printing feasible, the printhead cartridge H1000 of this embodiment includes independent color ink tanks, e.g., black, light cyan, light magenta, cyan, magenta, and yellow ink tanks. As shown in Fig. 4, these ink tanks can be independently attached to and detached from the printhead H1001.

As shown in an exploded perspective view of Fig. 5, the printhead H1001 comprises a printing element board H1100, first plate H1200, electrical printed circuit board H1300, second plate H1400, tank holder H1500, channel forming member H1600, filters H1700, and sealing rubber members H1800.

On the printing element board H1100, a plurality of printing elements for discharging ink and electric lines made of, e.g., Al for supplying electric power to these printing elements are formed on one surface of an Si substrate by film formation technologies. A plurality of ink channels and a plurality of discharge orifices

H1100T corresponding to the printing elements are formed by photolithography. Also, ink supply ports for supplying ink to these ink channels are formed in the rear surface. This printing element board H1100 is fixed
5 to the first plate H1200 by adhesion. Ink supply ports H1201 for supplying ink to the printing element board H1100 are formed in this first plate H1200. Furthermore, the second plate H1400 having an opening is fixed to the first plate H1200 by adhesion. This second plate H1400
10 holds the electric printed circuit board 1300 such that the electric printed circuit board H1300 and the printing element board H1100 are electrically connected.

This electric printed circuit board H1300 applies an electrical signal for discharging ink to the printing
15 element board H1100. The electric printed circuit board H1300 has electric lines corresponding to the printing element board H1100, and external signal input terminals H1301 formed in end portions of these electric lines to receive electrical signals from the main body. The
20 external signal input terminals H1301 are positioned and fixed at the back of the tank holder H1500.

The channel forming member H1600 is ultrasonically welded to the tank holder H1500 for detachably holding the ink tanks H1900, thereby forming ink channels H1501
25 from the ink tanks H1900 to the first plate H1200. Also, the filters H1700 are formed at those end portions of

the ink channels H1501, which engage with the ink tanks H1900, to prevent invasion of dust from the outside. The sealing rubber members H1800 are attached to the portions engaging with the ink tanks H1900 to prevent
5 evaporation of ink from these engaging portions.

Furthermore, the printhead H1001 is constructed by bonding, by an adhesive or the like, a tank holder unit composed of the tank holder H1500, channel forming member H1600, filters H1700, and sealing rubber members
10 H1800 to a printing element unit composed of the printing element board H1100, first plate H1200, electric printed circuit board H1300, and second plate H1400.

(Carriage)

15 The carriage M4001 will be described below with reference to Fig. 2.

As shown in Fig. 2, this carriage M4001 includes a carriage cover M4002 and head set lever M4007. The carriage cover M4002 engages with the carriage M4001 and
20 guides the printhead H1001 to the mount position of the carriage M4001. The head set lever M4007 engages with the tank holder H1500 of the printhead H1001 and pushes the printhead H1000 such that the printhead H1000 is set in a predetermined mount position.

25 That is, the head set lever M4007 is set in the upper portion of the carriage M4001 so as to be pivotal

about a head set level shaft. Also, a head set plate
(not shown) is set via a spring in a portion which
engages with the printhead H1001. By the force of this
spring, the printhead H1001 is pushed and mounted on the
5 carriage M4001.

A contact flexible print cable (to be referred
to as a contact FPC hereinafter) E0011 is set in another
engaging portion of the carriage M4001 with respect to
the printhead H1001. Contact portions E0011a on this
10 contact FPC E0011 and the contact portions (external
signal input terminals) H1301 formed on the printhead
H1001 electrically contact each other to exchange
various pieces of information for printing or supply
electric power to the printhead H1001.

15 An elastic member (not shown) made of, e.g.,
rubber is formed between the contact portions E0011a of
the contact FPC E0011 and the carriage M4001. The
elastic force of this elastic member and the biasing
force of the head set lever spring make reliable contact
20 between the contact portions E0011a and the carriage
M4001 possible. Furthermore, the contact FPC E0011 is
connected to a carriage printed circuit board E0013
mounted on the back surface of the carriage M4001
(Fig. 7).

25 [Scanner]

The printer of this embodiment is also usable as a reading apparatus by replacing the printhead with a scanner.

This scanner moves together with the carriage of
5 the printer and reads an original image supplied instead of a printing medium in a sub-scan direction. Information of one original image is read by alternately performing the read operation and the original feed operation.

10 Figs. 6A and 6B are views showing an outline of the arrangement of this scanner M6000.

As shown in Figs. 6A and 6B, a scanner holder M6001 has a box-like shape and contains optical systems and processing circuits necessary for reading. A scanner
15 read lens M6006 is placed in a portion which faces the surface of an original when this scanner M6000 is mounted on the carriage M4001. This scanner read lens M6006 reads an original image. A scanner illuminating lens M6005 contains a light source (not shown), and
20 light emitted by this light source irradiates an original.

A scanner cover M6003 fixed to the bottom portion of the scanner holder M6001 so fits as to shield the interior of the scanner holder M6001 from light.
25 Louver-like handles formed on the side surfaces of this scanner cover M6003 facilitate attachment to and

detachment from the carriage M4001. The external shape of the scanner holder M6001 is substantially the same as the printhead cartridge H1000. So, the scanner holder M6001 can be attached to and detached from the carriage
5 M4001 by operations similar to the printhead cartridge H1000.

Also, the scanner holder M6001 accommodates a board having the processing circuits described above and a scanner contact PCB M6004 connected to this board and
10 exposed to the outside. When the scanner M6000 is mounted on the carriage M4001, this scanner contact PCB M6004 comes in contact with the contact FPC E0011 of the carriage M4001, thereby electrically connecting the board to the control system of the main body via the
15 carriage M4001.

An electric circuit configuration in this embodiment of the present invention will be described next.

Fig. 7 is a view schematically showing the overall
20 arrangement of an electric circuit in this embodiment.

The electric circuit of this embodiment primarily comprises the carriage printed circuit board (CRPCB) E0013, a main PCB (Printed Circuit Board) E0014, and a power supply unit E0015.

25 The power supply unit is connected to the main PCB E0014 to supply various driving power.

The carriage printed circuit board E0013 is a printed circuit board unit mounted on the carriage M4001 (Fig. 2) and functions as an interface for exchanging signals with the printhead through the contact FPC E0011.

5 Also, on the basis of a pulse signal output from an encoder sensor E0004 in accordance with the movement of the carriage M4001, the carriage printed circuit board E0013 detects changes in the positional relationship between an encoder scale E0005 and the encoder sensor
10 E0004 and outputs a signal to the main PCB E0014 through a flexible flat cable (CRFFC) E0012.

The main PCB is a printed circuit board unit for controlling driving of individual parts of the inkjet printing apparatus of this embodiment. This main PCB has,
15 on the board, I/O ports for, e.g., a paper end sensor (PE sensor) E0007, an ASF sensor E0009, a cover sensor E0022, a parallel interface (parallel I/F) E0016, a serial interface (serial I/F) E0017, the resume key E0019, the LED E0020, the power key E0018, and the
20 buzzer E0021. The main PCB is also connected to a CR motor E0001, an LF motor E0002, and a PG motor E0003 to control driving of these motors. Additionally, the main PCB has interfaces connecting to an ink end sensor E0006, a GAP sensor E0008, a PG sensor E0010, a CRFFC E0012,
25 and the power supply unit E0015.

Fig. 8 is a block diagram showing the internal arrangement of the main PCB.

Referring to Fig. 8, a CPU E1001 internally has an oscillator OSC E1002 and is connected to an oscillation circuit E1005 to generate a system clock by an output signal E1019 from the oscillation circuit E1005. Also, the CPU E1001 is connected to a ROM E1004 and an ASIC (Application Specific Integrated Circuit) E1006. In accordance with programs stored in the ROM E1004, the CPU E1001 controls the ASIC and senses the statuses of an input signal E1017 from the power key, an input signal E1016 from the resume key, a cover sensing signal E1042, and a head sensing signal (HSENS) E1013. Additionally, the CPU E1001 drives the buzzer E0021 by a buzzer signal (BUZ) E1018 and senses the statuses of an ink end sensing signal (INKS) E1011 and a thermistor temperature sensing signal (TH) E1012 connected to a built-in A/D converter E1003. Furthermore, the CPU E1001 controls driving of the inkjet printing apparatus by performing various logic operations and condition judgements.

The head sensing signal E1013 is a head mounting sensing signal which the printhead cartridge H1000 inputs via the flexible flat cable E0012, the carriage printed circuit board E0013, and the contact flexible print cable E0011. The ink end sensing signal is an

output analog signal from the ink end sensor E0006. The thermistor temperature sensing signal E1012 is an analog signal from a thermistor (not shown) formed on the carriage printed circuit board E0013.

5 A CR motor driver E1008 is supplied with motor power (VM) E1040 as a driving source. In accordance with a CR motor control signal E1036 from the ASIC E1006, the CR motor driver E1008 generates a CR motor driving signal E1037 to drive the CR motor E0001. An LF/PG motor
10 driver E1009 is also supplied with the motor power E1040 as a driving source. In accordance with a pulse motor control signal (PM control signal) E1033 from the ASIC E1006, the LF/PG motor driver E1009 generates an LF motor-driving signal E1035 to drive the LF motor and
15 also generates a PG motor driving signal E1034 to drive the PG motor.

 A power control circuit E1010 controls power supply to each sensor having a light-emitting element, in accordance with a power control signal E1024 from the
20 ASIC E1006. The parallel I/F E0016 transmits a parallel I/F signal E1030 from the ASIC E1006 to a parallel I/F cable E1031 connected to the outside, and transmits signals from this parallel I/F cable E1031 to the ASIC E1006. The serial IF E0017 transmits a serial I/F signal
25 E1028 from the ASIC E1006 to a serial I/F cable E1029

connected to the outside, and transmits signals from this cable E1029 to the ASIC E1006.

The power supply unit E0015 supplies head power (VH) E1039, the motor power (VM) E1040, and logic power (VDD) E1041. A head power ON signal (VHON) E1022 and a motor power ON signal (VMOM) E1023 from the ASIC E1006 are input to the power supply unit E0015 to control ON/OFF of the head power E1039 and the motor power E1040, respectively. The logic power (VDD) E1041 supplied from the power supply unit E0015 is subjected to voltage transformation where necessary and supplied to individual units inside and outside the main PCB E0014.

The head power E1039 is smoothed on the main PCB E0014, supplied to the flexible flat cable E0011, and used to drive the printhead cartridge H1000.

A reset circuit E1007 detects a decrease in the logic power-supply voltage E1040 and supplies a reset signal (RESET) E1015 to the CPU E1001 and the ASIC E1006 to initialize them.

This ASIC E1006 is a one-chip semiconductor integrated circuit which is controlled by the CPU E1001 via a control bus E1014, outputs the CR motor control signal E1036, the PM control signal E1033, the power control signal E1024, the head power ON signal E1022, and the motor power ON signal E1023, and exchanges signals with the parallel I/F E10016 and the serial I/F

E0017. Also, the ASIC E1006 senses the statuses of a PE sensing signal (PES) E1025 from the PE sensor E0007, an ASF sensing signal (ASFS) E1026 from the ASF sensor E0009, a GAP sensing signal (GAPS) E1027 from the GAP
5 sensor E0008, and a PG sensing signal (PGS) E1032 from the PG sensor E0010, and transmits data indicating the statuses to the CPU E1001 through the control bus E1014. On the basis of the input data, the CPU E1001 controls driving of the LED driving signal E1038 to turn on and
10 off the LED E0020.

Furthermore, the ASIC E1006 senses the status of an encoder signal (ENS) E1020 to generate a timing signal and interfaces with the printhead cartridge H1000 by a head control signal E1021, thereby controlling a
15 printing operation. The encoder signal (ENC) E1020 is an output signal from the CR encoder sensor E0004, that is input through the flexible flat cable E0012. The head control signal E1021 is supplied to the printhead cartridge E1000 through the flexible flat cable E0012,
20 the carriage printed circuit board E0013, and the contact FPC E0011.

Fig. 9 is a block diagram showing the internal arrangement of the ASIC E1006.

Referring to Fig. 9, only flows of data, such as
25 printing data and motor control data, pertaining to control of the head and each mechanical part are shown

in connections between individual blocks. Control signals and clocks concerning read and write of a built-in register in each block and control signals related to DMA control are omitted to avoid the
5 complexity of description in the drawing.

As shown in Fig. 9, a PLL E2002 generates a clock (not shown) to be supplied to the most part of the ASIC E1006, in accordance with a clock signal (CLK) E2031 and PLL control signal (PLLON) E2033 output from the CPU
10 E1001.

A CPU interface (CPU I/F) E2001 controls read and write to a register in each block (to be described below), supplies clocks to some blocks, and accepts an interrupt signal (none of these functions is shown), in
15 accordance with the reset signal E1015, a soft reset signal (PDWN) E2032 and the clock signal (CLK) E2031 output from the CPU E1001, and a control signal from the control bus E1014. This CPU I/F E2001 outputs an interrupt signal (INT) E2034 to the CPU E1001 to inform
20 the CPU E1001 of generating an interrupt in the ASIC E1006.

A DRAM E2005 has areas such as a receiving buffer E2010, work buffer E2011, print buffer E2014, and expanding data buffer E2016, as printing data buffers,
25 and also has a motor control buffer E2023 for motor control. In addition to these printing data buffers, the

DRAM E2005 has areas such as a scanner loading buffer E2024, scanner data buffer E2026, and sending buffer E2028, as buffers for use in a scanner operation mode.

This DRAM E2005 is also used as a work area
5 necessary for the operation of the CPU E1001. That is, a
DRAM controller E2004 switches between access from the
CPU E1001 to the DRAM E2005 using the control bus and
access from a DMA controller E2003 (to be described
below) to the DRAM E2005, thereby performing read and
10 write to the DRAM E2005.

The DMA controller E2003 accepts a request (not
shown) from each block and outputs, to the RAM
controller, an address signal and a control signal
(neither is shown), or write data (E2038, E2041, E2044,
15 E2053, E2055, or E2057) when a write operation is to be
performed, thereby performing DRAM access. When a read
operation is to be performed, the DMA controller E2003
transfers readout data (E2040, E2043, E2045, E2051,
E2054, E2056, E2058, or E2059) from the DRAM controller
20 E2004 to the block which has requested.

A 1284 I/F E2006 interfaces by two-way
communication with an external host apparatus (not
shown) through the parallel I/F E0016 under the control
of the CPU E1001 via the CPU I/F E2001. Also, when
25 printing is to be performed, the 1284 I/F E2006
transfers received data (PIF received data E2036) from

the parallel I/F E0016 to a reception controller E2008
by DMA processing. When scanner read is to be performed,
the 1284 I/F E2006 transmits data (1284 transmission
data (RDPIF) E2059) stored in the sending buffer E2028
5 in the DRAM E2005 to the parallel I/F by DMA processing.

A USB I/F E2007 interfaces by two-way
communication with an external host apparatus (not
shown) through the serial I/F E0017 under the control of
the CPU E1001 via the CPU I/F E2001. Also, when printing
10 is to be performed, the USB I/F E2007 transfers received
data (USB received data E2037) from the serial I/F E0017
to the reception controller E2008 by DMA processing.
When scanner read is to be performed, the USB I/F E2007
transmits data (USB transmission data (RDPIF) E2058)
15 stored in the sending buffer E2028 in the DRAM E2005 to
the serial I/F by DMA processing. The reception
controller E2008 writes received data (WDIF) E2038) from
a selected one of the 1284 I/F E2006 and the USB I/F
E2007 into a receiving buffer write address managed by a
20 receiving buffer controller E2039.

A compression·expansion DMA E2009 reads out, under
the control of the CPU E1001 via the CPU I/F E2001,
received data (raster data) stored on the receiving
buffer E2010 from a receiving buffer read address
25 managed by the receiving buffer controller E2039,
compresses or expands readout data (RDWK) E2040 in

accordance with a designated mode, and writes the data as a printing code string (WDWK) E2041 in the work buffer area.

5 A printing buffer transfer DMA E2013 reads out, under the control of the CPU E1001 via the CPU I/F E2001, printing codes (RDWP) E2043 on the work buffer E2011, rearranges each printing code into an address on the print buffer E2014, which is suitable for the order of data transfer to the printhead cartridge H1000, and
10 transfers the code (WDWP E2044). A work clear DMA E2012 repeatedly transfers and writes, under the control of the CPU E1001 via the CPU I/F E2001, designated work file data (WDWF) E2042 in a region on the work buffer to which the data is completely transferred by the printing
15 buffer transfer DMA E2015.

A printing data expanding DMA E2015 reads out, under the control of the CPU E1001 via the CPU I/F E2001, the printing codes rearranged and written on the print buffer and expanding data written on the expanding data
20 buffer E2016, by using a data expansion timing signal E2050 from a head controller E2018 as a trigger, thereby generating expanded printing data (WDHDG) E2045, and writes the generated data as column buffer write data (WDHDG) E2047 in a column buffer E2017. This column
25 buffer E2017 is an SRAM for temporarily storing data (expanded printing data) to be transferred to the

printhead cartridge H1000. The column buffer E2017 is shared and managed by the printing data expanding DMA and the head controller in accordance with a handshake signal (not shown) of these two blocks.

5 Under the control of the CPU E1001 via the CPU I/F E2001, this head controller E2018 interfaces with the printhead cartridge H1000 or the scanner via a head control signal. In addition, on the basis of a head driving timing signal E2049 from an encoder signal
10 processor E2019, the head controller E2018 outputs a data expansion timing signal E2050 to the printing data expanding DMA.

When printing is to be performed, the head controller E2018 reads out expanded printing data (RDHD)
15 E2048 from the column buffer in accordance with the head driving timing signal E2049. The head controller E2018 outputs the readout data to the printhead cartridge H1000 via the head control signal E1021.

In a scanner read mode, the head controller E2018
20 transfers loaded data (WDHD) E2053 input via the head control signal E1021 to the scanner loading buffer E2024 on the DRAM E2005 by DMA transfer. A scanner data processing DMA E2025 reads out, under the control of the CPU E1001 via the CPU I/F E2001, loading buffer readout
25 data (RDAV) E2054 stored in the scanner loading buffer E2024 into a scanner data buffer E2026 on the DRAM E2005

and writes processed data (WDAV) E2055, subjected to processing such as averaging, into the scanner data buffer E2016 on the DRAM E2005.

A scanner data compressing DMA E2027 reads out
5 processed data (RDYC) E2056 on the scanner data buffer E2026, compresses the data, and writes compressed data (WDYC) E2057 in the sending buffer E2028, under the control of the CPU E1001 via the CPU I/F E2001.

The encoder signal processor E2019 receives an
10 encoder signal (ENC) and outputs the head driving timing signal E2049 in accordance with a mode determined by the control of the CPU E1001. In addition, the encoder signal processor E2019 stores information concerning the position or speed of the carriage M4001, obtained from
15 the encoder signal E1020, into a register and provides the information to the CPU E1001. On the basis of this information, the CPU E1001 determines various parameters for controlling the CR motor E0001. A CR motor controller E2020 outputs a CR motor control signal E1036
20 under the control of the CPU E1001 via the CPU I/F E2001.

A sensor signal processor E2022 receives output sensing signals from, e.g., the PG sensor E0010, the PE sensor E0007, the ASF sensor E0009, and the GAP sensor E0008, and transmits these pieces of sensor information
25 to the CPU E1001 in accordance with a mode determined by the control of the CPU E1001. The sensor signal

processor E2022 also outputs a sensor signal E2052 to an LF/PG motor control DMA E2021.

Under the control of the CPU E1001 via the CPU I/F E2001, this LF/PG motor control DMA E2021 reads out a pulse motor driving table (RDPM) E2051 from a motor control buffer E2023 on the DRAM E2005 and outputs a pulse motor control signal E. In addition, the LF/PG motor control DMA E2021 outputs a pulse motor control signal E1033 by using the abovementioned sensor signal as a trigger of the control.

An LED controller E2030 outputs an LED driving signal E1038 under the control of the CPU E1001 via the CPU I/F E2001. A port controller E2029 outputs the head power ON signal E1022, the motor power ON signal E1023, and the power control signal E1024 under the control of the CPU E1001 via the CPU I/F E2001.

The operation of the inkjet printing apparatus of this embodiment of the present invention constructed as above will be described below with reference to a flow chart in Fig. 10.

When this apparatus is connected to the AC power supply, in step S1 first initialization is performed for the apparatus. In this initialization, the electric circuit system including, e.g., the ROM and RAM of this apparatus is checked, thereby checking whether the apparatus can normally operate electrically.

In step S2, whether the power key E0018 on the upper case M1002 of the apparatus main body M1000 is pressed is checked. If the power key E0018 is pressed, the flow advances to step S3 to perform second
5 initialization.

In this second initialization, the various driving mechanisms and the head system of this apparatus are checked. That is, whether the apparatus is normally operable is checked in initializing the various motors
10 and loading head information.

In step S4, an event is waited for. That is, a command event from the external I/F, a panel key event by a user operation, or an internal control event with respect to this apparatus is monitored. If any of these
15 events occurs, processing corresponding to the event is executed.

For example, if a printing command event is received from the external I/F in step S4, the flow advances to step S5. If a power key event by a user
20 operation occurs in step S4, the flow advances to step S10. If another event occurs in step S4, the flow advances to step S11.

In step S5, the printing command from the external I/F is analyzed to determine the designated paper type,
25 sheet size, printing quality, and paper feed method. Data indicating these determination results is stored in

the RAM E2005 of the apparatus, and the flow advances to step S6.

In step S6, paper feed is started by the paper feed method designated in step S5. When the sheet is fed to a printing start position, the flow advances to step S7.

In step S7, printing is performed. In this printing, printing data supplied from the external I/F is once stored in the printing buffer. Subsequently, the CR motor E0001 is driven to start moving the carriage M4001 in the scanning direction, and the printing data stored in the print buffer E2014 is supplied to the printhead cartridge H1000 to print one line. When the printing data of one line is completely printed, the LF motor E0002 is driven to rotate an LF roller M3001 to feed the sheet in the sub-scan direction. After that, the above operation is repeatedly executed. When printing of the printing data of one page supplied from the external I/F is completed, the flow advances to step S8.

In step S8, the LF motor E0002 is driven to drive a sheet delivery roller M2003. Sheet feed is repeated until it is determined that the sheet is completely delivered from this apparatus. When this operation is completed, the sheet is completely delivered onto the sheet delivery tray M1004a.

In step S9, whether printing of all pages to be printed is completed is checked. If pages to be printed remain, the flow returns to step S5 to repeat the operation in steps S5 to S9 described above. When
5 printing of all pages to be printed is completed, the printing operation is completed. After that, the flow returns to step S4 to wait for the next event.

In step S10, a printer termination process is performed to stop the operation of this apparatus. That
10 is, to shut off the power supply to the various motors and the head, the operation transits to a state in which the power supply can be shut off. After that, the power supply is shut off, and the flow returns to step S4 to wait for the next event.

15 In step S11, event processing other than the above is performed. For example, processing corresponding to any of the diverse panel keys of this apparatus, a recovery command from the external I/F, or an internally occurring recovery event is performed. After the
20 processing, the flow advances to step S4 to wait for the next event.

[First Embodiment]

○ Summary of Head Control

Common ink discharge is performed by ANDing
25 printing data and a heat pulse. Printing data determines the presence/absence of printing. A heat pulse involves

in control of discharge energy. Also, driving all dischargeable nozzles at the same time excessively increases the electric power, generated heat amount, and ink supply amount. Therefore, discharge nozzles are usually separately driven.

First, a discharge nozzle driving circuit and driving timings of the first embodiment will be described below with reference to Figs. 11 and 12.

Fig. 11 is a view showing the discharge nozzle driving circuit of the first embodiment. Fig. 12 is a timing chart showing the driving timings of this discharge nozzle driving circuit shown in Fig. 11.

Fig. 11 shows a printhead having sixty-four nozzles divided into eight portions by an 8-bit shift register 103 and three block division signals. Each heater 101 is driven by a transistor. When this heater 101 is heated, film boiling occurs in ink, so the ink can be discharged.

Printing data is serially transferred to the shift register 103 by using an HCLK signal and an Si signal and latched by a latch 102 by using a BG signal. A decoder 100 decodes three block division signals, i.e., signals BE0, BE1, BE2 into eight signals which are enable signals (block designation signals) of the heater 101 divided into eight portions. Discharge is controlled

by ANDing a printing data signal, a selected block designation signal, and a heat pulse signal HE.

A power supply path in a general inkjet printing apparatus will be described below with reference to

5 Fig. 13.

Fig. 13 is a view showing a power supply path of a general inkjet printing apparatus.

An electric current supplied in the form of a pulse to a heater of a printhead 302 is smoothed by an
10 electrolytic capacitor 301a on a CR printed circuit board 301. Accordingly, although the electric current for driving the printhead 302 causes voltage drop by an intermediate wiring resistance, this current functions as a pulse current from the CR printed circuit board 301
15 to the printhead 302 and functions as a smoothed current from the CR printed circuit board 301 to a main power supply 300, thereby causing an intermediate voltage drop.

When this voltage drop occurs, a pulse width must be increased to supply the same energy to the heater.

20 Assume that a printing apparatus has a common power supply system and mounts a printhead having 64 nozzles per chip x 4 colors. When this printhead is driven by dividing one chip into eight blocks, the number of simultaneous ink discharging nozzles as a whole is 0 to
25 32 (8 dots/chip x 4 chips). Assume that the number of simultaneous ink discharging nozzles is uniform with

respect to the nozzle positions in each chip and is also uniform timewise. In this case, if the number of simultaneous ink discharging nozzles is N, a power supply circuit is schematically considered as a parallel circuit of heater resistances as shown in Fig. 14.

In this circuit, a wiring resistance for each of these heaters 1 to N in the printhead varies in accordance with the distance from an electrode of the printhead to the heater. To prevent this, it is desirable to design wiring in the printhead by adjusting the wiring width such that the wiring resistances for the heaters are the same.

When the voltage drop caused by simultaneous discharge is compensated for by the driving pulse width as described above, the relationship between the number of simultaneous ink discharging nozzles and the driving pulse width is represented as in Fig. 15.

An unknown driving pulse width table for determining the driving pulse width, which table has been examined prior to the present invention, has determined a driving pulse width by the various driving conditions (heater resistance and driving transistor resistance (TrON resistance)) of the printhead, the wiring resistances, and the environmental temperature. For example, Fig. 16 shows a driving pulse width table when the heater resistance and the TrON resistance are

divided into eight ranks and the environmental temperature is divided into five ranks from 20°C or less to 50°C or more.

In this table, the influence of the voltage drop
5 by the number of simultaneous ink discharging nozzles is neglected. Hence, the driving pulse width is so set as to compensate for ink discharge when the number of simultaneous ink discharging nozzles is a maximum. This increases the design load for minimizing the voltage
10 drop. Especially when the number of simultaneous ink discharging nozzles is small, excess energy is applied to the heater, and this adversely affects the durability of the printhead. By contrast, Fig. 17 shows an unknown driving pulse width table including the number of
15 simultaneous ink discharging nozzles.

This method can avoid supplying excess energy when the number of simultaneous ink discharging nozzles is small. However, the method requires heater ranks (8 ranks) x TrON ranks (8 ranks) x environmental
20 temperature ranks (5 ranks) = 320 driving pulse width tables. Consequently, a large memory area in a memory for storing the driving pulse width tables is consumed.

In the first embodiment, therefore, driving pulse width tables as shown in Figs. 18 to 20 are formed.
25 First, a driving pulse No. is determined in accordance with the printhead driving conditions. In this

embodiment, the driving pulse for the printhead is determined (Fig. 18) a driving condition using the environmental temperature in addition to the printhead characteristics such as the heater rank and TrON rank, and a fundamental pulse width for driving is determined (Fig. 19). In this case, the environmental temperature may be a head temperature obtained from a temperature sensor arranged on a head constituent member such as a printing element board, or a head temperature estimated using a temperature sensor arranged outside the head. Subsequently, on the basis of this driving pulse No., a driving pulse width table (Fig. 20) for correcting the voltage drop by the number of simultaneous ink discharging nozzles is determined. Accordingly, pulses having the same fundamental pulse width and equal pulse width compensation amounts based on the number of simultaneous ink discharging nozzles have the same driving pulse No. serving as an index No. This makes it possible to design a small driving pulse width table as shown in Fig. 20 by avoiding unnecessary duplication. Also, pulses having the same fundamental pulse width and different pulse width compensation amounts are assigned different driving pulse Nos., such as driving pulse Nos. 15 and 16.

A method of discriminating the number of simultaneous ink discharging nozzles (the number of

simultaneously driven heaters) in real time will be described below with reference to Fig. 21.

Fig. 21 is a block diagram of a driving signal generating circuit of the first embodiment. Fig. 22 is a timing chart showing the driving timings of this driving signal generating circuit shown in Fig. 21.

Assuming one block period is a basis, printing data is transferred in one block period, and nozzles corresponding to the transferred printing data are driven in the next period. Therefore, Fig. 21 will be described on the basis of a synchronous trigger.

When a synchronous trigger is input, printing data to be transferred is loaded from a printing buffer and latched in a printing data latch 1102. At the same time, a block switch 1100 switches block signals, and a clock signal generator 1101 generates a clock HCLK signal for transferring the latched printing data to the printhead. More specifically, the number of bits of the latched printing data is added. If the block period has a margin, an easy addition method is to enable the printing data and count up a counter by the HCLK signal. If there is no time margin, it is also possible to add all bits by an adder and completely discriminate the number of simultaneous ink discharging nozzles while the printing data is transferred.

A pulse generator 1105 outputs a heat pulse signal HE by modulating the pulse width. One example of the pulse width modulation method is to store the driving pulse width table shown in Fig. 20 into a RAM, read out a modulation amount requiring the number of simultaneous ink discharging nozzles as an address from the driving pulse width table, and use the readout modulation amount in pulse width modulation. In this pulse width modulation, a necessary pulse width can be obtained by outputting H after an elapse of a time designated by the synchronous trigger, and outputting L after an elapse of a designated time, in this example, a time read out from the driving pulse width table.

In this example, the fundamental pulse for driving is generated using the printhead characteristics such as the heater rank and TrON rank. However, the fundamental pulse may be generated using either the heater rank or the TrON rank. Alternatively, this fundamental pulse may be generated in consideration of wiring resistances and manufacturing errors in, e.g., heater surface heater size. The generated printhead fundamental driving pulse can be measured and written as a head ROM set No. in a storage means, e.g., an EEPROM of the printhead, so as to be used as a means for obtaining a driving pulse No. instead of the head characteristics such as heater rank·TrON rank. Furthermore, as shown in Fig. 23, it is

possible to form a driving pulse width table which manages the rise time and fall time of the heat pulse signal HE, while the fall time of a fundamental pulse is fixed. In this example, the block start time is 0, and
5 the rise-fall set No. which is an integral multiple of the pulse resolution is described. This eliminates the trouble to calculate the rise time and fall time from the driving pulse width table. Figs. 24 to 28 show the arrangements of driving pulse width tables in this case.

10 Processing executed in the first embodiment will be described below with reference to Fig. 29.

Fig. 29 is a flow chart showing the processing executed in the first embodiment.

In processing of the flow chart, steps S101 to
15 S103 are executed before printing or if a time margin is sufficient during line return or the like, while steps S104 and S105 are executed during printing (head driving).

In step S101, a heater rank and TrON rank serving as the
20 printhead characteristics, and environmental temperature are detected. In step S102, on the basis of the detected heater rank, TrON rank, and environmental temperature, a driving pulse No. is determined by looking up the table shown in Fig. 18. In step S103, a fundamental pulse
25 width corresponding to the determined driving pulse No. is determined by looking up the table shown in Fig. 19.

In step S104, the number of simultaneous ink discharging nozzles of the printhead to be processed is discriminated. In step S105, a modulation amount of the fundamental pulse width, which corresponds to the discriminated number of simultaneous ink discharging nozzles, is determined by looking up the table shown in Fig. 20, and the fundamental pulse width is modulated by this modulation amount to generate a driving pulse.

Note that the above processing is realized by the aforementioned main PCB (E0014) shown in Fig. 8 by controlling the individual components shown in Fig. 21 by looking up the driving pulse width tables shown in Figs. 18 to 20.

In the first embodiment as described above, the fundamental pulse width is determined by the driving conditions such as the printhead characteristics and environmental temperature. After that, the driving pulse width is determined by the number of simultaneous ink discharging nozzles and the fundamental pulse width. Accordingly, pulse width control for correcting the voltage drop caused by an increase in the number of simultaneous ink discharging nozzles can be appropriately performed even when the pulse width changes with temperature change. Also, it is possible to prevent printing density unevenness and landing errors caused by temperature change and at the same time

improve the durability by performing pulse width control based on the number of simultaneous ink discharging nozzles.

In the first embodiment, to improve both the discharge stability and the heater durability, a reduction in the input energy to the heater caused by the voltage drop by the number of simultaneous ink discharging nozzles is compensated for by the pulse width. However, this first embodiment is similarly applicable to a case in which a short pulse for holding the temperature, not for discharging ink, is input.

[Second Embodiment]

In the second embodiment, control of the driving pulse width in an inkjet printing apparatus having a plurality of printheads will be described.

In this embodiment, assume that the number of printheads is two.

A power supply path of an inkjet printing apparatus in which a power supply system is divided into two parts and power is separately supplied to two printheads will be described below with reference to Fig. 30.

Fig. 30 is a view showing a power supply path of the inkjet printing apparatus of the second embodiment.

In this apparatus, three numbers of simultaneous ink discharging nozzles exist: the number S1 of

simultaneous ink discharging nozzles for a printhead 2002, the number S2 of simultaneous ink discharging nozzles for a printhead 2003, and the total number S3 (= S1 + S2) of simultaneous ink discharging nozzles.

5 Strictly, a voltage drop with respect to the printhead 2002 is affected by the resistances of C-11 and C-12, the number S1 of simultaneous ink discharging nozzles, the resistance of a current smoothing portion, and the total number S3 of simultaneous ink discharging nozzles.

10 Driving pulse width control taking account of all these factors is complicated. Therefore, the resistance value of the current smoothing portion is designed to be low, and the number of simultaneous ink discharging nozzles of each power supply system is counted assuming that the

15 degree of a voltage drop (by the resistances of C-11 and C-12 and the number S1 of simultaneous ink discharging nozzles) primarily caused by a pulse current is large. In this manner, a driving pulse width for compensating for voltage drops in the lines C-11 and C-12 caused by

20 simultaneous discharge is determined. If the two power supply systems are different in, e.g., the head driving voltage, the number of nozzles, the discharge amount, or the driving pulse width, preparing different driving pulse width tables for these systems makes the present

25 invention adaptable.

Also, when a plurality of chips of the same driving conditions are used in a single printhead as shown in Fig. 31, the printhead is so designed that wiring resistances are equal from a power input terminal D1 to power input terminals A11, A12, B11, and B12 of the printhead (analogously, from a GND terminal D2 to A21, A22, B21, and B22). That is, since the numbers of simultaneous ink discharging nozzles of the power supply systems are totaled, the durability or the discharge performance varies in accordance with the nozzle position if there is a voltage drop difference resulting from the nozzle position. If chips having different driving conditions are present, e.g., if the sizes of printhead heaters are different, it is possible to use separate power supply lines for these chips as described above, or to make voltage drops (= (current value) x (wiring resistance)) equal to each other by using wiring resistances.

The average number of simultaneous ink discharging nozzles presumably has a certain upper limit when limitations on an ink implantation amount with respect to a printing medium or division of a printing pass is taken into consideration. That is, although the number of simultaneous ink discharging nozzles exceeding this upper limit is possible in a certain instant, the average number of simultaneous ink discharging nozzles

is not so large. Hence, voltage drops are suppressed to be low by capacitor components, and driving is performed by an excess driving pulse width.

To avoid this, this upper limit is set to be the
5 number of simultaneous ink discharging nozzles = 16. An increase in the pulse width caused by this number of simultaneous ink discharging nozzles is, as shown in Fig. 32, so designed as to be suppressed to about 60 to 80% of a pulse width obtained by a driving pulse
10 calculation for the upper limit (16) of the number of simultaneous ink discharging nozzles or more. Fig. 33 shows a driving pulse width table in this case.

This upper limit of the number of simultaneous ink discharging nozzles also changes in accordance with a
15 printing mode in multi-pass printing for performing printing complementarily using a plurality of passes in the main scanning direction of the head (in four passes, 25% is MAX for each color; in eight passes, 12.5%). Accordingly, it is effective to change the position at
20 which this pulse width is deviated from a calculated value or change the deviation of a driving pulse in accordance with a printing mode by changing the upper limit of the number of simultaneous ink discharging nozzles.

25 Fig. 34 shows an example in which the number of simultaneous ink discharging nozzles is uniformly

distributed to chips and heaters. In a case like this,
the effect of compensating for voltage drops by control
of the driving pulse width according to the present
invention is large. On the other hand, if discharge is
5 concentrated to one chip owing to a printing mode or in
one-pass printing as shown in Fig. 35, a wiring
resistance in a portion indicated by the thick line in
Fig. 35 is no longer negligible. This induces a large
voltage drop for the same number of simultaneous ink
10 discharging nozzles. To prevent this, it is effective to
change the driving pulse width table in accordance with
a printing mode, e.g., increase the driving pulse width
only in one-pass printing. Alternatively, since the
number of simultaneous ink discharging nozzles is -
15 limited to 0 to 8 in one-pass printing (in the second
embodiment), it is effective to increase the pulse width
only when the number of simultaneous ink discharging
nozzles is 8 or less as shown in Fig. 36, without
changing the table in accordance with a printing mode.
20 When this is the case, a driving pulse width table is as
shown in Fig. 37.

When the voltage drop changes depending on the
number of simultaneous ink discharging nozzles for each
printing mode such as the number of passes or the number
25 of colors used, the optimal driving pulse width must
preferably be changed for each printing mode. In the

table system (Fig. 20) for setting the pulse width
itself for pulse width correction for compensating the
voltage drop by the number of simultaneous ink
discharging nozzles for the driving pulse No. determined
5 by the heater rank and TrON rank of the printhead and
the environmental temperature, the table shown in
Fig. 20 must be prepared for each printing mode to
increase the table capacity. In Fig. 20, the number of
driving pulses is 16, and the number of ranks of the
10 number of simultaneous ink discharging nozzles is 4. If
the number of printhead chips increases to increase the
number of simultaneous ink discharging nozzles, this
increases the number of ranks of the simultaneous ink
discharging nozzles. The capacity of the table for each
15 printing mode inevitably increases. To solve this
problem, the table configuration in Fig. 27 is employed
in place of the table contents in Fig. 20 in which the
pulse width is directly designated. The table in Fig. 27
stores the simultaneous ink discharging pulse No. in the
20 form of an index No. representing the table contents as
a combination of the driving pulse No. and the number of
simultaneous ink discharging nozzles. In addition,
another table is prepared to store the relationship
between the simultaneous ink discharging pulse No. and
25 the P2 set value for setting the fall time of the pulse
width. More specifically, only one table (Fig. 27)

representing the driving pulse No. and the number of simultaneous ink discharge nozzles is prepared, while the table (Fig. 38) representing the relationship between the number of simultaneous ink discharging pulse No. and the P2 set value is prepared for each printing mode. The optimal pulse width can be set for each printing mode without increasing the table capacity. In this case, since the simultaneous ink discharging pulse No. is merely an index No. for determining the P2 set value, the correlation between the No. value and the pulse width is not always required. All "0"s are assigned to the discharge range of 0 to 7 as the number of simultaneous ink discharge nozzles for the driving pulse Nos. 1 to 4 in Fig. 27. Assume that the same pulse width must be set in a printing mode A, and that different pulse widths must be set for the driving pulse Nos. 1 and 2 and the driving pulse Nos. 3 and 4 in a printing mode B. Using a driving pulse No. and a simultaneous ink discharging pulse No. (No. 20 in this case) not used in the table of simultaneous ink discharging pulse Nos., a table having the contents shown in Fig. 39 is prepared. The table representing the relationship between the simultaneous ink discharging pulse No. and the P2 set value for each mode is replaced with a table shown in Fig. 40, thereby allowing optimal control for each printing mode without

increasing the table content as much as possible.

In discharge such as predischARGE, a discharge pattern entirely different from patterns in printing is often used. Therefore, also in this predischARGE it is effective to change the driving pulse width table. Alternatively, if the number of simultaneous ink discharging nozzles in predischARGE is limited, it is effective to increase the pulse width for the number of simultaneous ink discharging nozzles smaller than the limit. In predischARGE, a discharge pattern is often limited to full-nozzle discharge. In this case, the number of simultaneous ink discharging nozzles remains the same. Hence, a fixed pulse can be used without controlling the driving pulse width by the number of simultaneous ink discharging nozzles according to the present invention.

In the second embodiment as described above, a driving pulse width table corresponding to the specifications of a printing apparatus is generated, and a driving pulse is generated by using this table. Accordingly, pulse width control for correcting a voltage drop caused by an increase in the number of simultaneous ink discharging nozzles can be appropriately performed even when the pulse width changes with temperature change. It is also possible to prevent printing density unevenness or landing errors

due to temperature change and at the same time improve the durability by performing pulse width control on the basis of the number of simultaneous ink discharging nozzles.

5 The above embodiments have been explained by assuming that a droplet discharged from a printhead is ink and that a liquid contained in an ink tank is ink. However, the content of the ink tank is not limited to ink. For example, the ink tank can also contain a
10 processing solution to be discharged onto a printing medium to increase the fixing properties, water resistance, or quality of a printed image.

 The above embodiments can increase the density and resolution of printing by using a system which includes
15 a means (e.g., an electrothermal transducer or a laser beam) for generating thermal energy as energy used to discharge ink and causes a state change of the ink by this thermal energy, among other inkjet printing systems.

 As a representative arrangement or principle, it
20 is preferable to use the basic principle disclosed in, e.g., U.S.P. No. 4723129 or 4740796. This system is applicable to both a so-called on-demand apparatus and continuous apparatus. The system is particularly effective in an on-demand apparatus because at least one
25 driving signal which corresponds to printing information and which gives a rapid temperature rise exceeding

nuclear boiling is applied to an electrothermal transducer which corresponds to a sheet or channel holding a liquid (ink), thereby causing this electrothermal transducer to generate thermal energy and
5 cause film boiling on the thermal action surface of a printhead, and consequently a bubble can be formed in the liquid (ink) in one-to-one correspondence with the driving signal. By growth and shrinkage of this bubble, the liquid (ink) is discharged from a discharge orifice
10 to form at least one droplet. This driving signal is more preferably a pulse signal because growth and shrinkage of a bubble are instantaneously appropriately performed, so discharge of the liquid (ink) having high response is achieved.

15 This pulse driving signal is preferably a signal described in U.S.P. No. 4463359 or 4345262. Note that superior printing can be performed by the use of conditions described in U.S.P. No. 4313124 which is the invention concerning the rate of temperature rise on the
20 thermal action surface.

The arrangement of a printhead can be the combination (a linear liquid channel or a right-angle liquid channel) of the discharge orifices, liquid channels, and electrothermal transducers disclosed in
25 the specifications described above. The present invention also includes arrangements using

U.S.P. Nos. 4558333 and 4459600 in each of which the thermal action surface is placed in a bent region. Additionally, it is possible to use an arrangement based on Japanese Patent Laid-Open No. 59-123670 in which a
5 common slot is used as a discharge portion of a plurality of electrothermal transducers or Japanese Patent Laid-Open No. 59-138461 in which an opening for absorbing the pressure wave of thermal energy is opposed to a discharge portion.

10 Furthermore, a full line type printhead having a length corresponding to the width of the largest printing medium printable by a printing apparatus can have a structure which meets this length by combining a plurality of printheads as disclosed in the
15 aforementioned specifications or can be a single integrated printhead.

In addition, it is possible to use not only a cartridge type printhead, explained in the above embodiments, in which ink tanks are integrated with a
20 printhead itself, but also an interchangeable chip type printhead which can be electrically connected to an apparatus main body and supplied with ink from the apparatus main body when attached to the apparatus main body.

25 Adding a recovering means or a preliminary means for a printhead to the printing apparatus described

above is preferable because printing can further stabilize. Practical examples of the additional means for a printhead are a capping means, a cleaning means, a pressurizing or drawing means, and an electrothermal transducer or another heating element or a preliminary heating means combining them. A predischARGE mode for performing discharge different from printing is also effective to perform stable printing.

A recording mode of the printing apparatus is not restricted to a printing mode using only a main color such as black. That is, the apparatus can have at least a composite color mode using different colors and a full color mode using mixed colors, regardless of whether a printhead is an integrated head or the combination of a plurality of heads.

The above embodiments are explained assuming that ink is a liquid. However, it is possible to use ink which solidifies at room temperature or less but softens or liquefies at room temperature. In inkjet systems, the general approach is to perform temperature control such that the viscosity of ink falls within a stable discharge range by adjusting the temperature of the ink itself within the range of 30°C to 70°C. Hence, ink need only be a liquid when a printing signal used is applied to it.

Additionally, to positively prevent a temperature rise by thermal energy by positively using this temperature rise as energy of the state change from the solid state to the liquid state of ink, or to prevent evaporation of ink, ink which solidifies when left to stand and liquefies when heated can be used. That is, the present invention is applicable to any ink which liquefies only when thermal energy is applied, such as ink which liquefies when applied with thermal energy corresponding to a printing signal and is discharged as liquid ink, or ink which already starts to solidify when arriving at a printing medium. As described in Japanese Patent Laid-Open No. 54-56847 or 60-71260, this type of ink can be held as a liquid or solid in a recess or through hole in a porous sheet and opposed to an electrothermal transducer in this state. In the present invention, executing the aforementioned film boiling scheme is most effective for each ink described above.

Furthermore, the printing apparatus according to the present invention can take the form of any of an integrated or separate image output terminal of an information processing apparatus such as a computer, a copying apparatus combined with a reader or the like, and a facsimile apparatus having a transmission/reception function.

The present invention can be applied to a system constituted by a plurality of devices (e.g., a host computer, interface, reader, and printer) or to an apparatus (e.g., a copying machine or facsimile
5 apparatus) comprising a single device.

Further, the object of the present invention can also be achieved by providing a storage medium storing program codes of software for performing the aforesaid functions according to the embodiments to a system or an
10 apparatus, reading the program codes with a computer (or a CPU or MPU) of the system or apparatus from the storage medium, and then executing the program codes.

In this case, the program codes read out from the storage medium realize the functions according to the
15 embodiments, and the storage medium storing the program codes constitutes the invention.

Further, as the storage medium for providing the program codes, it is possible to use, e.g., a floppy disk, hard disk, optical disk, magnetooptical disk,
20 CD-ROM, CD-R, magnetic tape, nonvolatile memory card, and ROM.

Furthermore, besides aforesaid functions according to the above embodiments are realized by executing the program codes which are read out by a computer, the
25 present invention includes a case where an OS (Operating System) or the like running on the computer performs a

part or the whole of actual processing in accordance with designations by the program codes and realizes functions according to the above embodiments.

Furthermore, the present invention also includes a case where, after the program codes read out from the storage medium are written in a memory of a function extension board inserted into a computer or of a function extension unit connected to a computer, a CPU or the like of the function extension board or function extension unit performs a part or the whole of actual processing in accordance with designations by the program codes and realizes functions of the above embodiments.

When the present invention is applied to the above storage medium, this storage medium stores program codes corresponding to the flow chart shown in Fig. 29 explained earlier.

As many apparently widely different embodiments of the present invention can be made without departing from the spirit and scope thereof, it is to be understood that the invention is not limited to the specific embodiments thereof except as defined in the appended claims.

WHAT IS CLAIMED IS

1. A printing apparatus for performing printing by using a printhead having a plurality of printing elements, comprising:

5 discriminating means for discriminating the number of simultaneously driven printing elements of said plurality of printing elements when printing data is printed; and

control means for controlling a driving pulse to
10 be applied to printing elements used in the printing of the printing data, on the basis of a fundamental pulse width changeably determined on the basis of driving conditions of said printhead and the number of simultaneously driven printing elements discriminated by
15 said discriminating means.

2. The apparatus according to claim 1, wherein the driving conditions include a wiring resistance, heater resistance, driving TrON resistance, and environmental temperature of said printhead.

20 3. The apparatus according to claim 1, wherein said control means comprises:

storage means for storing a first management table for managing the correspondence of the driving conditions with the fundamental pulse width, and a
25 second management table for managing the correspondence of the fundamental pulse width with a change amount of

the fundamental pulse width based on the number of simultaneously driven printing elements;

first determining means for determining a fundamental pulse width corresponding to the driving conditions by looking up the first management table; and

second determining means for determining a change amount of the fundamental pulse width, which corresponds to the number of simultaneously driven printing elements, by looking up the second management table, and

changes the fundamental pulse width determined by said first determining means by the change amount determined by said second determining means to generate a driving pulse to be applied to printing elements used in the printing of the printing data.

4. The apparatus according to claim 1, wherein said control means defines the fundamental pulse width by one of leading and trailing edges of a pulse signal on the basis of the driving conditions, and controls a driving pulse width of a driving pulse to be applied to printing elements by the other, on the basis of the number of simultaneously driven printing elements.

5. The apparatus according to claim 4, wherein said control means comprises storage means for storing a third management table for managing the correspondence of rise time and fall time of the heat pulse, the driving conditions, and the fundamental pulse width, and

controls a pulse width of the driving pulse corresponding to the number of simultaneously driven printing elements and the driving conditions by looking up the third management table.

- 5 6. The apparatus according to claim 1, wherein said printing apparatus comprises a plurality of printheads, and

if power lines for supplying power to said printheads are independent of each other, said control
10 means executes the control for each power line.

7. The apparatus according to claim 1, wherein said control means makes a change amount for the driving pulse, which said control means generates by changing a pulse width of the fundamental pulse when the number of
15 simultaneously driven printing elements is not less than a predetermined value, smaller than a change amount for the driving pulse, which said control means generates by changing a pulse width of the fundamental pulse when the number of simultaneously driven printing elements is
20 less than the predetermined value.

8. The apparatus according to claim 1, wherein said control means makes a change amount for the driving pulse, which said control means generates by changing a pulse width of the fundamental pulse when the number of
25 simultaneously driven printing elements is not more than a predetermined value, larger than a change amount for

the driving pulse, which said control means generates by changing a pulse width of the fundamental pulse when the number of simultaneously driven printing elements is less than the predetermined value.

5 9. The apparatus according to claim 1, wherein if the number of simultaneously driven printing elements for use in predischarge of said printhead is limited, said control means makes a pulse width of a driving pulse to be applied to printing elements used in the predischarge
10 larger than a pulse width of a driving pulse to be applied to printing elements for use in printing which uses printing elements not less than the number of simultaneously driven printing elements.

10. The apparatus according to claim 1, wherein when
15 predischarge of said printhead is to be performed, said control means applies a driving pulse having a predetermined width to printing elements used in the predischarge.

11. The apparatus according to claim 1, wherein said
20 printing element is an ink discharge unit comprising an electrothermal transducer for discharging ink by generating a bubble in the ink by heat and a discharge orifice.

12. A method of controlling a printing apparatus for
25 performing printing by using a printhead having a plurality of printing elements, comprising:

the discrimination step of discriminating the number of simultaneously driven printing elements of said plurality of printing elements when printing data is printed; and

- 5 the control step of controlling a driving pulse to be applied to printing elements used in the printing of the printing data, on the basis of a fundamental pulse width changeably determined on the basis of driving conditions of said printhead and the number of
- 10 simultaneously driven printing elements discriminated in the discrimination step.

13. The method according to claim 12, wherein the driving conditions include a wiring resistance, heater resistance, driving TrON resistance, and environmental

15 temperature of said printhead.

14. The method according to claim 12, wherein the control step comprises:

- the storage step of storing a first management table for managing the correspondence of the driving
- 20 conditions with the fundamental pulse width, and a second management table for managing the correspondence of the fundamental pulse width with a change amount of the fundamental pulse width based on the number of simultaneously driven printing elements;

the first determination step of determining a fundamental pulse width corresponding to the driving conditions by looking up the first management table; and

the second determination step of determining a
5 change amount of the fundamental pulse, which corresponds to the number of simultaneously driven printing elements, by looking up the second management table, and

comprises changing the fundamental pulse width
10 determined in the first determination step by the change amount determined in the second determination step to generate a driving pulse to be applied to printing elements used in the printing of the printing data.

15. The method according to claim 12, wherein, the
15 control step comprises defining the fundamental pulse width by one of leading and trailing edges of a pulse signal on the basis of the driving conditions, and controlling a driving pulse width of a driving pulse to be applied to printing elements by the other, on the
20 basis of the number of simultaneously driven printing elements.

16. The method according to claim 15, wherein the control step comprises the storage step of storing a third management table for managing the correspondence
25 of rise time and fall time of the heat pulse, the driving conditions, and the fundamental pulse width, and

comprises controlling a pulse width of the driving pulse corresponding to the number of simultaneously driven printing elements and the driving conditions by looking up the third management table.

- 5 17. The method according to claim 12, wherein said printing apparatus comprises a plurality of printheads, and

if power lines for supplying power to said printheads are independent of each other, the control
10 step comprises executing the control for each power line.

18. The method according to claim 12, wherein the control step comprises making a change amount for the driving pulse, which the control step generates by changing a pulse width of the fundamental pulse when the
15 number of simultaneously driven printing elements is not less than a predetermined value, smaller than a change amount for the driving pulse, which the control step generates by changing a pulse width of the fundamental pulse when the number of simultaneously driven printing
20 elements is less than the predetermined value.

19. The method according to claim 12, wherein the control step comprises making a change amount for the driving pulse, which the control step generates by changing a pulse width of the fundamental pulse when the
25 number of simultaneously driven printing elements is not more than a predetermined value, larger than a change

amount for the driving pulse, which the control step generates by changing a pulse width of the fundamental pulse when the number of simultaneously driven printing elements is less than the predetermined value.

5 20. The method according to claim 12, wherein if the number of simultaneously driven printing elements for use in predischARGE of said printhead is limited, the control step comprises making a pulse width of a driving pulse to be applied to printing elements used in the
10 predischARGE larger than a pulse width of a driving pulse to be applied to printing elements for use in printing which uses printing elements not less than the number of simultaneously driven printing elements.

21. The method according to claim 12, wherein when
15 predischARGE of said printhead is to be performed, the control step comprises applying a driving pulse having a predetermined width to printing elements used in the predischARGE.

22. The method according to claim 12, wherein said
20 printing element is an ink discharge unit comprising an electrothermal transducer for discharging ink by generating a bubble in the ink by heat and a discharge orifice.

23. A computer-readable memory storing program codes
25 of control of a printing apparatus for performing

printing by using a printhead having a plurality of printing elements, comprising:

a program code of the discrimination step of discriminating the number of simultaneously driven printing elements of said plurality of printing elements when printing data is printed; and

a program code of the control step of controlling a driving pulse to be applied to printing elements used in the printing of the printing data, on the basis of a fundamental pulse width changeably determined on the basis of driving conditions of said printhead and the number of simultaneously driven printing elements discriminated in the discrimination step.

24. The apparatus according to claim 1, wherein the fundamental pulse width is a fundamental pulse width selected and determined from a plurality of fundamental pulse widths.

25. The apparatus according to claim 1, wherein the driving conditions are conditions including printhead characteristics.

26. The apparatus according to claim 3, wherein said second management table holds as an index value a change in fundamental pulse width which is based on the number of simultaneously driven printing elements.

27. The apparatus according to claim 26, characterized by further comprising a fourth management table

representing a relationship between the change in
fundamental pulse width and the index value, the fourth
management table being prepared for each printing mode.

28. The apparatus according to claim 27, wherein the
5 printing mode is a mode for performing printing
complementarily in accordance with a printing pass count.

29. The method for controlling a printing apparatus
according to claim 12, wherein the fundamental pulse
width is a fundamental pulse width selected and
10 determined from a plurality of fundamental pulse widths.

30. The method according to claim 12, wherein the
driving conditions are conditions including printhead
characteristics.

31. The method according to claim 14, wherein said
15 second management table holds as an index value a change
in fundamental pulse width which is based on the number
of simultaneously driven printing elements.

32. The method according to claim 30, characterized by
further comprising a fourth management table
20 representing a relationship between the change in
fundamental pulse width and the index value, the fourth
management table being prepared for each printing mode.

33. The method according to claim 32, wherein the
printing mode is a mode for performing printing
25 complementarily in accordance with a printing pass count.

ABSTRACT OF THE DISCLOSURE

When printing data is to be printed, the number of simultaneously driven printing elements of a plurality of printing elements of a printhead is discriminated. On
5 the basis of the number of simultaneously driven printing elements discriminated and a fundamental pulse width changeably, determined on the basis of driving conditions of the printhead, a driving pulse to be applied to printing elements used in the printing of the
10 printing data is controlled.

FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8





FIG.

LP/PG MOTOR DRIVER E0017






FIG. 11





FIG. 12







FIG. 14

FIG. 15




FIG. 16

HEATER RANK	TrON RANK	TEMPERATURE RANK	DRIVING PULSE WIDTH
1	1	~20°C	1.5
		~30°C	1.4
		~40°C	1.3
		~50°C	1.2
		50°C OR MORE	1.1
	2	~20°C	1.6
		~30°C	1.5
		~40°C	1.4
:	:	:	:
:	:	:	:
:	:	:	:
8	8	~20°C	2.9
		~30°C	2.8
		~40°C	2.7
		~50°C	2.6
		50°C OR MORE	2.4

FIG. 17

THE NUMBER OF SIMULTANEOUS INK DISCHARGING NOZZLES						
			0 ~ 7	~ 15	~ 23	~ 31
HEATER RANK	TrON RANK	TEMPERATURE RANK				
1	1	~20℃	1.2	1.3	1.4	1.5
		~30℃	1.1	1.2	1.3	1.4
		~40℃	1	1.1	1.2	1.3
		~50℃	0.9	1	1.1	1.2
		50℃ OR MORE	0.8	0.9	1	1.1
	2	~20℃	1.3	1.4	1.5	1.6
		~30℃	1.2	1.3	1.4	1.5
		~40℃	1.1	1.2	1.3	1.4
⋮	⋮	⋮	⋮	⋮	⋮	⋮
⋮	⋮	⋮	⋮	⋮	⋮	⋮
⋮	⋮	⋮	⋮	⋮	⋮	⋮
8	8	~20℃	2.2	2.4	2.6	2.9
		~30℃	2.2	2.4	2.6	2.8
		~40℃	2.2	2.3	2.5	2.7
		~50℃	2	2.2	2.3	2.6
		50℃ OR MORE	1.9	2.1	2.2	2.4

8×8×5=320

FIG. 19

DRIVING PULSE No.	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
FUNDAMENTAL PULSE WIDTH (μ S)	0.8	0.9	1	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2	2.1	2.2	2.2

FIG. 20

DRIVING PULSE No.	THE NUMBER OF SIMULTANEOUS INK DISCHARGING NOZZLES			
	0~7	~15	~23	~32
1	0	0.1	0.2	0.3
2	0	0.1	0.2	0.3
3	0	0.1	0.2	0.3
4	0	0.1	0.2	0.3
5	0	0.1	0.2	0.4
6	0	0.1	0.3	0.4
7	0	0.1	0.3	0.4
8	0	0.2	0.3	0.4
9	0	0.1	0.3	0.5
10	0	0.1	0.3	0.5
11	0	0.2	0.4	0.5
12	0	0.2	0.3	0.5
13	0	0.2	0.3	0.6
14	0	0.2	0.4	0.6
15	0	0.2	0.4	0.6
16	0	0.2	0.4	0.7


FIG. 21

FIG. 22




FIG. 23




FIG. 24

HEAD ROM SET No. — PULSE WIDTH (AT 20 ~ 30°C)	
HEAD ROM SET No.	PULSE WIDTH
1	0.6
2	0.7
3	0.8
4	0.9
:	:
:	:
:	:
:	:

FIG. 25

HEAD ROM SET No. — DRIVING PULSE No. CORRESPONDENCE TABLE

HEAD ROM SET No.	TEMPERATURE RANK					
	~20°C	~30°C	~40°C	~50°C	~50°C OR MORE	
4	5	4	3	2	1	
5	6	5	4	3	2	
6	7	6	5	4	3	
7	8	7	7	5	4	
:	:	:	:	:	:	
:	:	:	:	:	:	
:	:	:	:	:	:	
:	:	:	:	:	:	

↑ NUMBER IS DRIVING PULSE No.

FIG. 26

DRIVING PULSE No. — P1 SET VALUE

DRIVING PULSE No.	P1	PULSE WIDTH
1	14	0.6
2	13	0.7
3	12	0.8
4	11	0.9
:	:	:
:	:	:
:	:	:
:	:	:

FIG. 27

DRIVING PULSE No. — SIMULTANEOUS INK DISCHARGING PULSE No.

DRIVING PULSE No.	THE NUMBER OF SIMULTANEOUS INK DISCHARGING NOZZLES			
	0~7	~15	~23	~32
1	0	3	6	9
2	0	3	6	9
3	0	3	7	9
4	0	4	7	10
:	:	:	:	:
:	:	:	:	:
:	:	:	:	:
:	:	:	:	:

↑ NUMBER IS SIMULTANEOUS DISCHARGING PULSE No.

SIMULTANEOUS INK DISCHARGING PULSE No. — P2 SET VALUE

SIMULTANEOUS INK DISCHARGING PULSE No.	P2	PULSE MODULATION WIDTH
0	20	0
1	21	0.1
2	22	0.2
3	23	0.3
4	24	0.4
⋮	⋮	⋮
⋮	⋮	⋮
⋮	⋮	⋮
⋮	⋮	⋮


FIG. 29

FIG. 30




FIG. 31




FIG. 32




FIG. 33

PULSE TABLE IN WHICH PULSE WIDTH IS NARROWED WHEN THE NUMBER OF SIMULTANEOUS INK DISCHARGING NOZZLES IS 16 OR MORE

DRIVING PULSE No.	THE NUMBER OF SIMULTANEOUS INK DISCHARGING NOZZLES			
	0~7	~15	~23	~32
1	0	0.1	0.1	0.2
2	0	0.1	0.2	0.2
3	0	0.1	0.2	0.3
4	0	0.1	0.2	0.3
5	0	0.1	0.2	0.3
6	0	0.1	0.2	0.3
7	0	0.1	0.2	0.3
8	0	0.2	0.2	0.3
9	0	0.1	0.3	0.3
10	0	0.1	0.3	0.3
11	0	0.2	0.2	0.3
12	0	0.2	0.3	0.4
13	0	0.2	0.3	0.4
14	0	0.2	0.3	0.4
15	0	0.2	0.3	0.5
16	0	0.2	0.3	0.5

FIG. 34

EXAMPLE IN WHICH THE NUMBER OF
SIMULTANEOUS INK DISCHARGING NOZZLES
= 8 IS UNIFORMLY DISTRIBUTED




FIG. 35

EXAMPLE IN WHICH THE NUMBER OF
SIMULTANEOUS INK DISCHARGING NOZZLES
= 8 IS CONCENTRATED TO ONE CHIP




FIG. 36




FIG. 37

EXAMPLE IN WHICH PULSE WIDTH IS INCREASED WHEN THE NUMBER OF
SIMULTANEOUS INK DISCHARGING NOZZLES IS 0 TO 7

DRIVING PULSE No.	THE NUMBER OF SIMULTANEOUS INK DISCHARGING NOZZLES			
	0~7	~15	~23	~32
1	0.1	0.1	0.1	0.2
2	0.1	0.1	0.2	0.2
3	0.1	0.1	0.2	0.3
4	0.1	0.1	0.2	0.3
5	0.1	0.1	0.2	0.3
6	0.1	0.1	0.2	0.3
7	0.1	0.1	0.2	0.3
8	0.1	0.2	0.2	0.3
9	0.1	0.1	0.3	0.3
10	0.1	0.1	0.3	0.3
11	0.1	0.2	0.2	0.3
12	0.1	0.2	0.3	0.4
13	0.2	0.2	0.3	0.4
14	0.1	0.2	0.3	0.4
15	0.2	0.2	0.3	0.5
16	0.2	0.2	0.3	0.5

FIG. 38

SIMULTANEOUS INK DISCHARGING PULSE No. — P2 SET VALUE

SIMULTANEOUS INK DISCHARGING PULSE No.	P2	PULSE MODULATION WIDTH
0	20	0
1	21	0.1
2	22	0.2
3	23	0.3
4	24	0.4
:	:	:
:	:	:
:	:	:
:	:	:

FOR PRINTING MODE A

SIMULTANEOUS INK DISCHARGING PULSE No. — P2 SET VALUE

SIMULTANEOUS INK DISCHARGING PULSE No.	P2	PULSE MODULATION WIDTH
0	21	0.1
1	22	0.2
2	23	0.3
3	24	0.4
4	25	0.5
:	:	:
:	:	:
:	:	:
:	:	:

FOR PRINTING MODE B

FIG. 39

DRIVING PULSE No. — SIMULTANEOUS INK DISCHARGING PULSE No.

DRIVING PULSE No.	THE NUMBER OF SIMULTANEOUS INK DISCHARGING NOZZLES			
	0~7	~15	~23	~32
1	0	3	6	9
2	0	3	6	9
3	20	3	7	9
4	20	4	7	10
:	:	:	:	:
:	:	:	:	:
:	:	:	:	:
:	:	:	:	:

FIG. 40

SIMULTANEOUS INK DISCHARGING PULSE No. — P2 SET VALUE

SIMULTANEOUS INK DISCHARGING PULSE No.	P2	PULSE MODULATION WIDTH
0	20	0
1	21	0.1
2	22	0.2
3	23	0.3
4	24	0.4
:	:	:
:	:	:
:	:	:
20	20	0

FOR PRINTING MODE A

SIMULTANEOUS INK DISCHARGING PULSE No. — P2 SET VALUE

SIMULTANEOUS INK DISCHARGING PULSE No.	P2	PULSE MODULATION WIDTH
0	21	0.1
1	22	0.2
2	23	0.3
3	24	0.4
4	25	0.5
:	:	:
:	:	:
:	:	:
20	22	0.2

FOR PRINTING MODE B

**COMBINED DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION**
(Page 1)

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled PRINTING APPARATUS, CONTROL METHOD OF THE APPARATUS, AND COMPUTER-READABLE MEMORY

the specification of which ☒ is attached hereto ☐ was filed on _____ as United States Application No. or PCT International Application No. _____ and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR §1.56.

I hereby claim foreign priority benefits under 35 U.S.C. §119(a)-(d) or §365(b), of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT international application which designates at least one country other than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate, or PCT international application having a filing date before that of the application on which priority is claimed:

Country	Application No.	Filed (Day/Mo./Yr.)	(Yes/No) Priority Claimed
Japan	11-237530	24 August 1999	Yes
Japan	2000-216265	17 July 2000	Yes
Japan	2000-219774	19 July 2000	Yes

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s), or § 365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 C.F.R. § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

Application No.	Filed (Day/Mo./Yr.)	Status (Patented, Pending, Abandoned)
-----------------	---------------------	---------------------------------------

I hereby appoint the practitioners associated with the firm and Customer Number provided below to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to the address associated with that Customer Number:

FITZPATRICK, CELLA, HARPER & SCINTO
Customer Number: 05514

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole or First Inventor Norihiro KAWATOKO

Inventor's signature _____

Date _____ Citizen/Subject of Japan

Residence c/o Canon Ryuseimukogaoka, 2-21-11, Shukugawara 2-chome,
Tama-ku, Kawasaki-shi, Kanagawa-ken, Japan

Post Office Address c/o CANON KABUSHIKI KAISHA, 30-2, Shimomaruko
3-chome, Ohta-ku, Tokyo, Japan

COMBINED DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION
(Page 2)

Full Name of Second Joint Inventor, if any Hiroshi TAJIKA

Second Inventor's signature _____

Date _____ Citizen/Subject of Japan

Residence 24-8-406, Kagahara 1-chome, Tsuzuki-ku, Yokohama-shi,
Kanagawa-ken, Japan

Post Office Address c/o CANON KABUSHIKI KAISHA, 30-2, Shimomaruko
3-chome, Ohta-ku, Tokyo, Japan

Full Name of Third Joint Inventor, if any Takayuki MURATA

Third Inventor's signature _____

Date _____ Citizen/Subject of Japan

Residence 2-13, Ikuta 2-chome, Tama-ku, Kawasaki-shi, Kanagawa-ken,
Japan

Post Office Address c/o CANON KABUSHIKI KAISHA, 30-2, Shimomaruko
3-chome, Ohta-ku, Tokyo, Japan

Full Name of Fourth Joint Inventor, if any Yuji KONNO

Fourth Inventor's signature _____

Date _____ Citizen/Subject of Japan

Residence 3-4-203, Tsuchihashi 4-chome, Miyamae-ku, Kawasaki-shi,
Kanagawa-ken, Japan

Post Office Address c/o CANON KABUSHIKI KAISHA, 30-2, Shimomaruko
3-chome, Ohta-ku, Tokyo, Japan

MAW\vjw